





**UV Primer DY Pre-coating liquid  
for Metal 1000ml**

Lot no.: 2508T0441

**Compatible printheads:**

DX5 | DX7 | TX800 | XP600 | I3200 | I1600 | 4720 | 1390

**CAUTIONS:**

**Harmful for aquatic life. Causes skin and eye irritation. May cause an allergic skin reaction.**

**Personal Protective Equipment (PPE):**

- Wear eye protection (goggles or a face shield). Direct contact can cause serious and permanent eye damage.
- Do not use chemical-resistant protective gloves (e.g. nitrile). Use only a nitrile barrier.

**Safety Handling:**

- Avoid contact with skin and clothing.
- Do not touch the eye with bare skin. In case of contact, immediately wash skin with soap and water.
- Avoid contact with fire and heat sources.

**First Aid:**

- Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
- Skin Contact: Remove contaminated clothing and wash skin with soap and water.
- Inhalation: Move to fresh air immediately.

**Storage and Disposal:**

- Store in a tightly sealed container in a cool, dark, and dry place, away from sunlight.
- Dispose of this and empty containers in accordance with local chemical waste regulations.



---

A fém alapozó folyadék (UV Primer) egy speciális vegyi anyag, amely **tapadóhídként** szolgál az anyag felülete és az UV tinta között. Kulcsfontosságú eleme az UV nyomtatási folyamatnak a nehezen nyomtatható hordozókon.

Biztosítja az UV tinta **maximális tapadását** a sima, nem porózus fémfelületeken. Megakadályozza a nyomat hámlását, kopását és lepattogzását.

**Felhasználhatósági idő:** legalább 6 hónap

**Kompatibilis nyomtatófejek:** DX5 | DX7 | DX8 | TX800 | XP600 | I3200| I1600| 4720 | 1390